

Round Stitching Wire

We manufacture round stitching wire in standard dimensions of

| | | | | | |
|---------------|---------|---------------|---------|---------------|---------|
| Nr. 16 | 1,60 mm | Nr. 21 | 0,80 mm | Nr. 26 | 0,50 mm |
| Nr. 17 | 1,35 mm | Nr. 22 | 0,75 mm | Nr. 27 | 0,45 mm |
| Nr. 18 | 1,20 mm | Nr. 23 | 0,70 mm | Nr. 28 | 0,40 mm |
| Nr. 19 | 1,05 mm | Nr. 24 | 0,60 mm | Nr. 30 | 0,35 mm |
| Nr. 20 | 0,90 mm | Nr. 25 | 0,55 mm | | |

and special dimensions from 0.35 mm to 1.6 mm diameter

- as bright wire or with copper-coated, zinc-coated, tin-coated and coloured finish
- On all standard spools from 2 to 1,000 kg
- In spooled coils and catchweight coils up to 45 kg
- In drums from 40 to 300 kg

As a supplement to our product range, we also offer pay-off-systems



Flat Stitching Wire

We manufacture flat stitching wire in standard dimensions of

| | | | |
|----------------|----------------|-----------------|----------------|
| Nr. 0 | 0,70 x 0,30 mm | Nr. V | 0,90 x 0,65 mm |
| Nr. I | 0,75 x 0,35 mm | Nr. VI | 0,97 x 0,78 mm |
| Nr. II | 0,75 x 0,45 mm | Nr. VII | 1,12 x 0,91 mm |
| Nr. III | 0,75 x 0,55 mm | Nr. VIII | 1,27 x 1,05 mm |
| Nr. IV | 0,80 x 0,65 mm | Nr. IX | 1,50 x 1,16 mm |



and in the corresponding special dimensions

- As bright wire or with copper-coated, zinc-coated or tin-coated finish
- On all standard spools from 2 to 20 kg
- In coils from 2 kg

Flat Ribbon Stitching Wire

We manufacture flat ribbon stitching wire in any desired dimensions:

| | | | |
|-------------|--------------|------------------|--------------|
| wide | 1,8 - 3,5 mm | thickness | 0,2 - 0,9 mm |
|-------------|--------------|------------------|--------------|

- As bright wire or with copper-coated or zinc-coated finish
- On all standard spools from 2 to 150 kg
- In coils from 2 to 60 kg



Other Stitching Wire Types

As a supplement to our stitching wire range, we also offer the following wire types:

- Crate stitching wire
- Paper staple wire
- Paper clip wire

- On all standard spools from 2 to 1,000 kg
- In spooled coils and catchweight coils up to 45 kg
- In drums from 40 to 300 kg